

# TTK 5600



The automatic packaging machine TTK 5600 (5600 - 5600 CS - 5600 MPE - 5600 MPS) are ideal for applications with a high production capacity. They can be used in multiple sectors, such as: food, retail, graphics and shipments, Mass Retailers, industrial and textile. These machines can be combined with a heat-shrinking tunnel such as TT40 & TT40 Twin.

Models	TTK 5600	TTK 5600 CS	TTK 5600 MPE	TTK 5600 MPS
Maximum product dimensions LxWxH (mm)	600 x 400 x 160	600 x 400 x 240	600 x 400 x 240	Length infinite x 400 x 240
Average packs per hour	0 - 2400	0 - 2400	0 - 3600	0 - 3600
Types of suitable film	Polyolefin, PVC, Polyethylene	Polyolefin, PVC, Polyethylene	Polyolefin, PVC, OPP, Polyethylene	Polyolefin
Film thickness	7 to 80 microns	7 to 80 microns	7 to 80 microns	7 to 80 microns
L-shaped sealing bar	Pneumatic feed 5 bar	Pneumatic feed 5 bar	Power supply (pneumatic connection is not required)	Power supply (pneumatic connection is not required)
Machine dimensions LxWxH (mm) with closed cover	2485 x 1245 x 1715	2485 x 1245 x 1715	2485 x 1245 x 1715	2244 x 1795 x 1726
Machine dimensions LxWxH (mm) with open cover	2485 x 1245 x 1900	2485 x 1245 x 1900	2485 x 1245 x 1900	2244 x 2395 x 1950